

Changing of MAC address using EEUPDATE

Modifies Omlex computer gigabit ethernet MAC address

Written By: Pavel Mazák

MS-DOS 7.10	Installation	n CD Menu	Made 1	by Wengier,	China DOS	Union.	2003
F1=Help							
	1) 2) 3) 4)	Install MS-DOS Boot froм Flopj Boot froм Hard Restart the sys	7.10 [] py Drive Drive stem	Enter] e			
Hit the key	of choice:						

Step 1 — Boot from MS-DOS boot CD

 K5-BOS 7.18 Installation CD Monu Made by Mengler, China BOS Union. 2003 K1=Help Install MS-BOS 7.18 [Enter] Boot from Floppy Drive Boot from Hard Drive Restart the system tit the key of choice: 	HS-DOS 7.18 Setup HS-DOS 7.18 Setup Helcome to HS-DOS 7.18 Setup. This micraf will help you to install HS-DOS 7.18 onto your system. Please click Next 13 continue, or click Cancel to close this mizard. (C)Copyright Microsoft Corp 1981-1999. Next Dancel	HS-BUS 7.18 Setup HS-BUS 7.18 Setup HS-BUS 7.18 Setup process is not complete. If you guit Setup non, HS-BUS 7.18 Hill not be properly installed. Are you sure you want to guit Setup? Yes Ho
	juus Setup	JUS Setup

- Insert DOS boot CD into DVD Drive
- Boot the computer
- Select 1 Install MS-DOS...
- Press Cancel on Dos Installation and confirm exitting

Step 2 — Find DVD ROM / EEUPDATE

MS-DOS 7.10 Setup	MS-DOS 7.10 Setup	
You have chosen to quit from MS-DOS 7.10 Setup. Please install it next time.	You have chosen to quit from MS-DOS 7.10 Setup. Please install it next time.	
(С)Copyright Microsoft Corp. 1981–1999. This program is Free Software under GNU GPL.	(C)Copyright Microsoft Corp. 1981–1999. This program is Free Software under GNU GPL.	
A : \>d :	A : >>d :	
	D:>>dir	
	Volume in drive D is EEUPDATE Directory of D:\	
	EEUPDATE EXE 604,795 09-17-2013 20:21 1 file(s) 604,795 bytes 0 dir(s) 0 bytes free 0 dir(s) 0 bytes free	

- Insert EEUPDATE DVD into DVD ROM
- Select DVD by typing D: into DOS Prompt. Note that DVD may have another letter. You may browse C:, E: etc, until you can confirm the directory contains EEUPDATE.EXE.
- To list directory contents, type DIR

Step 3 — Update MAC using EEUPDATE



- Invoke EEUPDATE.EXE by typing EEUPDATE and pressing ENTER. Tabulator may work to autocomplete the filename
- You should see Compatible NIC list that you can update select the one with MAC you want to modify
- To modify MAC, use: *EEUPDATE /NIC=x /MAC=aabbccddeeff*, where x is NIC ID from previous step, and aabbccddeeff is new MAC address in simple format without any separators
- Reboot the computer to apply settings by pressing CTRL+ALT+DEL, remove all disks from drives