OMLEX BIOS

Written By: Alejandro Pagán Albertos




INTRODUCTION

Configuration BIOS OMLEX.


© 2022


Step 1 — OMLEX BIOS



Enter **BIOS** click **DELETE**.


Step 2






- Configure **CPU**


Step 3






- Select **COMPATIBLE**
- Select **SATA Only**


Step 4






- Select **Hard Disk**
- Select as in the photo


Step 5



- Insert wisdom here.


Step 6






- Select **ATAPI CDROM**
- Select as in the photo


Step 7






- Insert wisdom here.


Step 8






- Select **Floppy Configuration**
- Select **1.44 MB ...**


Step 9






- Select **Super ID Configuration**
- Select **378**

Step 10







- Select **Normal**
- Select **IRQ7**

This document was generated on 2022-05-25 01:21:10 AM (MST).


Step 11






- Select **3F8/IRQ4**
- Select **Normal**

Step 12




- Select **2F8/IRQ3**


Step 13



- Select **Normal**


Step 14






- Select **Hardware Health Configuration**


Step 15






- Select **Power Configuration**


Step 16






- Select **ACPI Configuration**

Step 17



- Select **APM Configuration**


Step 18




ⓘ APM Configuration Step 17

- Select **Power On**
- Select **On/Off**


Step 19






- Select **Disabled**
- Select **Disabled**


Step 20






- Select **Disabled**
- Select **Disabled**


Step 21






- Select **Remote Access Configuration**
- Select **Disabled**

Step 22







- Select **USB Configuration**
- Select **Disabled**

This document was generated on 2022-05-25 01:21:10 AM (MST).


Step 23






- Select **iEi Feature**
- Select **Disabled**


Step 24






- Select everything as it is in the picture


Step 25



- Select **Boot Settings Configuration**


Step 26






- Select **Enabled**
- Select **Disabled**


Step 27






- Select **Force BIOS**
- Select **On**


Step 28



- Select **Disabled**


Step 29






- Select **Boot Device Priority**
- Select **CD7DVD-SM-ATAPI iHAS122 F**

Step 30







- Select **SATA: PM-WDC WD5003ABYZ-011FA0**
- Select **1st FLOPPY DRIVE**

This document was generated on 2022-05-25 01:21:10 AM (MST).


Step 31






- Select **Hard Disk Drives**
- Select **SATA:PM-WDC WD5003ABYZ-011FA0**

Step 32







- Select **Removable Drives**
- Select **1st FLOPPY DRIVE**

This document was generated on 2022-05-25 01:21:10 AM (MST).


Step 33






- Select **CD/DVD Drives**
- Select **CD/DVD: SM-ATAPI ....**

Step 34






- Select **Change Supervisor Password**
- Select **Change User Password**


This document was generated on 2022-05-25 01:21:10 AM (MST).


Step 35



- Select **North Bridge Configuration**


Step 36






- Select **Enabled**
- Select **Disabled**


Step 37






- Select **PCI/IGD**
- Select **Enabled. 128MB**

Step 38







- Select **Video Function Configuration**
- Select **CRT**

This document was generated on 2022-05-25 01:21:10 AM (MST).


Step 39






- Select **South Bridge Configuration**
- Select **Disabled**

Step 40



- Select **Disabled**

Step 41



- Exit Options